

XStream Series

»» Above-Ground Filter Systems

HIGH-CAPACITY SIZE FOR HIGH-QUALITY FILTRATION



XSTREAM® SERIES ABOVE-GROUND FILTER SYSTEM FEATURES

- » Extra-large filter body holds more dirt and debris and allows for more even distribution of particles throughout the filter cartridge, reducing maintenance and extending the filtration cycle
- » Quick-release, high-capacity air relief valve provides easy release of extra air for hassle-free filter operation
- » Glass-reinforced, noncorrosive filter tank provides all-weather durability
- » Easy-Lok™ ring design offers single-turn access to internal components
- » Quick-connect unions install with flexible or rigid plumbing
- » One-piece base provides safe, stable support



CC1000 ADDITIONAL FEATURES

- » 80 GPM flow rate
- » 100 ft² cartridge elements
- » PowerFlo Matrix® or PowerFlo® LX pump options



CC1500 ADDITIONAL FEATURES

- » 120 GPM flow rate
- » 150 ft² cartridge elements
- » PowerFlo Matrix or PowerFlo LX pump options

SPECIFICATIONS

Filter Type	Full-flow cartridge element		
Filter Tank	Injection-molded glass reinforced		
Filter Element	360° self-cleaning slotted laterals, precision installed in ball-joint assembly		
Fastenings	Easy-Lok ring assembly		
Mounting Base	Injection-molded glass reinforced		

FILTER PERFORMANCE DATA

FILTER NUMBER	EFFECTIVE FILTRATION AREA	DESIGN FLOW RATE	PRESSURE LOSS (AT DESIGN FLOW RATE)	MAXIMUM WORKING PRESSURE
CC1000	100 ft. ²	80 GPM	1 psi	35 psi
CC1500	150 ft. ²	120 GPM	1 psi	35 psi
	REQUIRED CLEARANCE		TURNOVER	
REPLACEMENT HAYWARD® CARTRIDGE	SIDE	ABOVE	8 HOURS	12 HOURS
CCX1000RE	18"	24"	38,400 gal	57,600 gal
CCX1500RE	18"	30"	57,600 gal	86,400 gal

» hayward.com » 1-888-HAYWARD

XStream Filters are listed by (when provided with a 3-foot twist-lock cord):



Pumps » Filters » Heating » Cleaners » Sanitization » Automation » Lighting » Water Effects » White Goods

